

FLEXTOOL PORTAVIBE® FVE44-2G — ENGINE GUARD

The Flextool PortaVibe provides the ultimate solution in concrete vibration. The new contoured engine protection guard offers improved durability and engine protection during operation and transport. The PortaVibe's heavy-duty yet lightweight design is highly portable and easy to operate. Fitted with an adjustable handle and carry strap for optimised operator comfort, and a reliable, quality Honda 4-stroke engine for hassle free operation.



Honda GX35 engine

Provides hassle free operation and low engine emissions

Contoured engine protection guard

- Improved durability and engine protection during operation and transport
- Protects critical engine components from concrete build-up



Convenient on/off switch and throttle

control built into the handle

Lightweight and balanced

- Heavy-duty yet lightweight design
- Highly portable
- Optimum manoeuvrability

Adjustable handle and carry strap

- Optimised operator comfort
 - Complete operator control

Flexshaft rubber support sleeve

For easier cleaning and improved support compared to metal springs

High-amplitude vibrating head

- For maximum efficiency and rapid consolidation of all types of concrete mixes
- Hardened steel for extended service life

HONDA

PRODUCT & PERFORMANCE SPECIFICATIONS



FLEXTOOL PORTAVIBE® CONCRETE VIBRATORS



FVE44-2 FVE4	4-20
--------------	------

Model	Nose Cap Type	Vibrator Head Diameter (mm)	Flexshaft Length (mm)	Operating Weight (kg)	Frequency (vib/min)	Amplitude in Air (mm)	Engine Make	Engine Model	Max Rated Power (Hp)	Fuel Type	Product Code
FVE44-2	Steel	44	540	11.5	9,000	2.8	Honda	GX35	1.5	Ô	FT201807-UNIT
FVE44-2G	Steel	44	540	12.5	9,000	2.8	Honda	GX35	1.5	ø	FT200036-UNIT







Engine Guard Front

Engine Guard Back



THE FLEXTOOL PROMISE

If the unexpected happens and something goes wrong with your Flextool equipment within the first 12 months of purchase, we'll arrange to give you a loan machine for 2 days, free of charge, while we work to repair or replace your Flextool product.*

flextool.com.au/flextool-promise

*Qualification criteria apply. Terms and conditions for the Flextool Promise can be found at flextool.com.au.

This Technical Data Sheet (TDS) summarises our best knowledge of the product, based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use of the product whether or not in accordance with any advice, specification, recommendation or information given by it.